

BABUS 6

Recessed optic IP rated downlight

design Roberto Mantovani



IP67-rated, recessed fixtures of the highest build quality, extremely compact dimensions and high output. Recessed optics guarantee high viewing comfort. Extra-clear tempered glass, ATEX cable gland, neoprene cable. Can also be installed with anti-glare filter for maximum viewing comfort.

Incassi IP67 di altissima qualità costruttiva, con dimensioni estremamente contenute ed elevati flussi luminosi. L'ottica arretrata garantisce un alto comfort visivo. Vetro extrachiaro temprato, pressacavo ATEX, cavo in neoprene. Equipaggiabili con filtro antiabbagliamento per il massimo comfort visivo.

Encastrables IP67 de très haute qualité constructive, avec des dimensions extrêmement contenues et flux lumineux élevés. L'optique en retrait garantit un confort visuel élevé. Verre extra-clair trempé, presse-étoupe ATEX, câble en néoprène. Peuvent être équipés avec filtre anti-éblouissement pour le meilleur confort visuel.



IP67 made in Italy

Einbau mit Schutzklasse IP67 mit hoher konstruktiver Qualität von extrem kleiner Größe und hohen Lichtströmen. Die Einbauoptik garantiert einen hohen visuellen Komfort. Extra gehärtetes Glas, ATEX Kabeldurchführung, Neopren-Kabel. Kann mit Blendschutzfilter ausgestattet werden für maximalen visuellen Komfort.

Empotrados IP67 de altísima calidad constructiva, con tamaño sumamente reducido y elevados flujos luminosos. La óptica retrocedida garantiza un alto confort visual. Vidrio ultraclaro templado, prensacables ATEX, cable de neopreno. Se pueden equipar con filtro antideslumbramiento para obtener el máximo confort visual.

Supply current

350-500mA (V, 8,7V)

Power

3-6W


Series wiring

CRI


85

2-Step MacAdam

Dimensions



Photometric diagrams




CCT/CRI/Flux

	350mA	500mA
2700K	267lm	384lm
3000K	279lm	400lm
4200K	309lm	462lm
6000K	342lm	495lm

Code construction


BT2 X X X



Accessories

CSBU01

Recessing box



LBT201

Low luminance louver



Note: The filter must be ordered together with the lighting fixture.

Drivers 350mA

on/off

AL1034 (1..3) IP20 30 mm

AL1035 (1..3) IP20 40 mm

AL1037 (1..5) IP20 S.P. 55 mm

AL9011 (1..4) IP67 44 mm

dimnable

AL4000 (1..4) IP20 PUSH 0/1..10V 72 mm

ALD435 (1..3) IP20 DALI 2 PUSH 36 mm

AL4051 (1..4) IP20 DALI 2 72 mm

AL4053 (1..4) IP20 PUSH IGBT-TRIAC 56 mm

AL6035 (1..3) IP67 DALI 2 44 mm

AL8035 (2..4) IP67 DALI 2 48 mm

Drivers 500mA

on/off

AL1074 (1..2) IP20 30 mm

AL1077 (1..2) IP20 40 mm

AL1084 (1..3) IP20 S.P. 55 mm

AL9051 (1..3) IP67 44 mm

dimnable

AL4010 (1..4) IP20 PUSH 0/1..10V 72 mm

ALD450 (1..2) IP20 DALI 2 PUSH 36 mm

AL4151 (1..4) IP20 DALI 2 72 mm

AL4153 (1..4) IP20 PUSH IGBT-TRIAC 56 mm

AL6050 (1..2) IP67 DALI 2 44 mm

AL8050 (2..4) IP67 DALI 2 48 mm