


BEAN

Steplight

design Roberto Mantovani



The Bean range offers IP67 asymmetrical emission devices of extremely compact dimensions, for ground or wall installation.

La gamma Bean propone apparecchi ad emissione asimmetrica IP67 di dimensioni estremamente ridotte, per installazione a terra o a parete.

La gamme Bean propose des appareils à émission asymétrique IP67 de dimensions extrêmement réduites, pour installation au sol ou au mur.



IP67 made in Italy

Die Bean-Serie bietet extrem kleine IP67-Asymmetrieleuchten für die Boden- oder Wandmontage.

La gama Bean propone aparatos de emisión asimétrica IP67 de dimensiones extremadamente pequeñas, para instalación en el suelo o en la pared.

Supply current
350mA (V_i 2,9V)


Power
1W

Series wiring


CRI
85

2-Step MacAdam

Dimensions



Photometric diagrams



CCT/CRI/Flux


2700K	101lm
3000K	109lm
4200K	116lm
6000K	132lm

Code construction

EA1	X	X					
	B	G	N	K	Z		
	White	Grey	Black	COR-TEN	INOX AISI 316L		
	0	1	2	3	6	7	8
	2700K	3000K	4200K	6000K	Blue	Green	Red

Accessories

CSLN01
Recessing box



Drivers 350mA

on/off

- AL1034** (1..11) IP20 30 mm
- AL1035** (1..11) IP20 40 mm
- AL1037** (1..16) IP20 S.P. 55 mm
- AL9011** (1..12) IP67 44 mm

dimnable

- AL4000** (1..12) IP20 PUSH 0/1..10V 72 mm
- ALD435** (1..11) IP20 DALI 2 PUSH 36 mm
- AL4051** (2..14) IP20 DALI 2 72 mm
- AL4053** (1..14) IP20 PUSH IGBT-TRIAC 56 mm
- AL6035** (2..8) IP67 DALI 2 44 mm
- AL8035** (4..16) IP67 DALI 2 48 mm