

CORE 6

Recessed optic downlights

design Lapo Grassellini



The Core recessed fixtures range matches the utmost performance to incredible compactness. Recessed optics ensure high visual comfort. Revolutionary in dissipative, functional design, it offers the possibility to combine colour temperatures and beam angles in CRI98 with R9 93 versions.

La gamma di incassi Core combina altissime prestazioni ad una dimensione incredibilmente contenuta. L'ottica arretrata garantisce un alto comfort visivo. Rivoluzionari per il design funzionale alla dissipazione, offrono la possibilità temperature colore ed aperture di fascio nelle versioni a CRI98 con R9 93.

La gamme d'encastrables Core associe prestations très élevées et dimension incroyablement contenue. L'optique en retrait garantit un confort visuel élevé. Révolutionnaires pour le design fonctionnel à la dissipation, ils offrent la possibilité de températures, couleur et ouvertures de faisceau dans les versions à CRI98 avec R9 93.



IP44 made in Italy

Die Einbauleuchterserie Core vereint höchste Leistung mit einer unglaublich kleinen Größe. Die Rückwärtsoptik garantiert hohen Sehkomfort. Revolutionär in ihrem funktionalen Design zur Dissipation, bieten sie die Möglichkeit, Temperaturen, Farben und Strahlöffnungen in den Versionen CRI98 mit R9 93 zu kombinieren.

La gama de luminarias empotrables Core combina un rendimiento muy alto con un tamaño increíblemente pequeño. La óptica hacia atrás garantiza un alto confort visual. Revolucionarios por el diseño funcional para la disipación, ofrecen la posibilidad de temperaturas de color y aperturas de haz en las versiones CRI98 con R9 93.

Supply current

500mA (V_i 9V)

Power

6W


Series wiring

CRI


98

2-Step MacAdam

Dimensions




Photometric diagrams



CCT/CRI/Flux

2700K	540 lm
3000K	600 lm
4000K	620 lm

Code construction



Accessories

LCE601

Low luminance louver



SCE601

Milky screen



Note: The filter and the screen must be ordered together with the lighting fixture.

AL7022

24VDC/500mA constant current converter

Drivers 500mA

on/off

AL1074 (1..2) IP20 30 mm

AL1077 (1..2) IP20 40 mm

AL1084 (1..3) IP20 S.P. 55 mm

dimnable

AL4010 (1..4) IP20 PUSH 0/1..10V 72 mm

ALD450 (1..2) IP20 DALI 2 PUSH 36 mm

AL4151 (1..4) IP20 DALI 2 72 mm

AL4153 (1..4) IP20 PUSH IGBT-TRIAC 56 mm