FLEXA LIGHTING

TUBE 6

Ceiling luminaires

AC CC

AC IP40 CC IP44 made in Italy

design Lapo Grassellini

The Tube 6 range of ceiling luminaires combines minimal geometry with a high level of mechanical and optical quality. The rearward optical system ensures elevated visual comfort. Equipped with COB Fidelity, it is designed for a CRI98 and R9 93.

La gamma di apparecchi a plafone Tube 6 combina una geometria minimale ad una qualità meccanica ed ottica di alto livello. L'ottica arretrata garantisce un alto comfort visivo. Equipaggiati con COB Fidelity si connota per un CRI98 e R9 93.

La gamme d'appareils pour plafonds Tube 6 associe géométrie minimale et qualité mécanique et optique de haut niveau. L'optique en retrait garantit un confort visuel élevé. Équipés de COB Fidelity, les appareils se caractérisent par un IRC98 et R9 93.

Die Deckenleuchten-Serie Tube 6 verbindet eine minimale Geometrie mit hoher mechanischer und optischer Qualität. Die Rückenoptik garantiert einen hohen Sehkomfort. Ausgestattet mit COB Fidelity ist sie für einen CRI98 und R9 93 konnotiert.

La gama de luminarias de techo Tube 6 combina una geometría minimalista con una alta calidad mecánica y óptica. La óptica hacia atrás garantiza un alto confort visual. Equipados con COB Fidelity se caracteriza por un CRI98 y R9 93.

Supply current
500mA (V_f 9V) **(CC)**
230VAC **(AC)**

Power
6W

Series wiring (CC)

CRI
98

2-Step MacAdam

Dimensions



Photometric diagrams



CCT/CRI/Flux

2700K — 540 lm
3000K — 600 lm
4000K — 620 lm

Code construction

TB6 X X X X

- **AC** — On board driver
- **CC** — Remote driver
- **2** — 2700K
- **3** — 3000K
- **4** — 4000K
- **1** — 35°
- **2** — 45°
- **1** — White
- **5** — Black

Accessories

LTB601
Low luminance louver

Note: The filter must be ordered together with the lighting fixture.

Drivers 500mA (CC version only)

on/off
AL1074 (1..2) IP20 30 mm
AL1077 (1..2) IP20 40 mm
AL1084 (1..3) IP20 S.P. 55 mm

dimmable
AL4010 (1..4) IP20 PUSH 0/1..10V 72 mm
ALD450 (1..2) IP20 DALI 2 PUSH 36 mm
AL4151 (1..4) IP20 DALI 2 72 mm
AL4153 (1..4) IP20 PUSH IGBT-TRIAC 56 mm

FLEXALIGHTING Srl via Lisbona 21, 50065 Pontassieve (FI) Italy t. +39.055.8323021 f. +39.055.8324866 info@flexalighting.it